


## DOWNLIGHT QUNA A MINI 940 11W 36° GREY PREMIUM WHITE ON/OFF

Article number: N211-K0001-PW940-HA-R36-ZC01\_250-S8-###



3 SDCM





LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

90 Led chip flux 1343 [lm]

Luminous flux

1074 [lm]

System power

Luminaire Efficiency

11 [W]
98 [Im/W]

Beam angle 36°

Controller ON/OFF

## LUMINAIRE

Weight 1,2 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour GREY
Cover Glass
Operating voltage 220-240V 50-60Hz

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska