

## DOWNLIGHT

## DOWNLIGHT QUNA A MINI 850 25W 36° GREY | ON/OFF

Article number: N211-K0001-RF850-H8-R36-ZC02\_650-S8-###





Ø150mm

LED		СОВ
Light cold	our	5000 [K]
CRI		80
Led chip	flux	3764 [lm]
Luminous	s flux	3011 [lm]
System p	power	25 [W]
Luminaire	e Efficiency	120 [lm/W]
Beam an	gle	36°
Controlle	r	ON/OFF
MacAdar	n	3 SDCM
LUMINAIRE		
Weight		1,2 [kg]

## Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

IP 20, IK 3,

220-240V 50-60Hz

GREY

Glass



Street: Ignatza Hakuby 18 41-914 Bytom, Polska