


## DOWNLIGHT QUNA A MINI 927 27W 24° GREY | ON/OFF

Article number: N211-K0001-RF927-H8-R24-ZC02\_700-S8-###







COB Light colour 2700 [K] | CRI Led chip flux 3111 [lm] Luminous flux 2488 [lm] System power 27 [W] Luminaire Efficiency 92 [lm/W] Beam angle 24° Controller ON/OFF MacAdam 3 SDCM

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

## LUMINAIRE

Weight 1,2 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour GREY
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska