

DOWNLIGHT QUNA A MINI 927 27W 36° GREY | ON/OFF

Article number: N211-K0001-RF927-H8-R36-ZC02_700-S8-###



LED	COB
Light colour	2700 [K]
CRI	80
Led chip flux	3111 [lm]
Luminous flux	2488 [lm]
System power	27 [W]
Luminaire Efficiency	92 [lm/W]
Beam angle	36°
Controller	ON/OFF
MacAdam	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

LUMINAIRE

Weight	1,2 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska