

# DOWNLIGHT QUNA A MINI 930 21W 36° BLACK HI EFFICIENT ON/OFF

Article number: N211-K0002-BB930-H8-R36-ZC02\_550-S8-###



LED	COB
Light colour	3000 [K] HI EFFICIENT
CRI	90
Led chip flux	3487 [lm]
Luminous flux	2789 [lm]
System power	21 [W]
Luminaire Efficiency	133 [lm/W]
Beam angle	36°
Controller	ON/OFF
MacAdam	3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

### LUMINAIRE

Weight	1,2 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska