


DOWNLIGHT QUNA A MINI 942 21W 15° BLACK MEAT WHITE ON/OFF

Article number: N211-K0002-CC942-H8-R15-ZC02_550-S8-###







LED COB

Light colour 4200 [K] MEAT WHITE

CRI

Led chip flux

Luminous flux

System power

Luminaire Efficiency

Beam angle

Controller

90

2159 [lm]

21727 [lm]

82 [lm/W]

82 [lm/W]

Controller

MacAdam

3 SDCM

LUMINAIRE

Weight 1,2 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska