

DOWNLIGHT QUNA A MINI 930 11W 15° BLACK PREMIUM WHITE ON/OFF

Article number: N211-K0002-HE930-HA-R15-ZC01_250-S8-###



LED	COB
Light colour	3000 [K]
CRI	PREMIUM WHITE
Led chip flux	90
Luminous flux	1497 [lm]
System power	1197 [lm]
Luminaire Efficiency	11 [W]

Beam angle 109 [lm/W]
Controller 15°

MacAdam ON/OFF 3 SDCM

LUMINAIRE

Weight 1.2 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.









Street: Ignatza Hakuby 18 41-914 Bytom, Polska