

DOWNLIGHT

DOWNLIGHT QUNA A MINI 935 11W 60° BLACK PREMIUM WHITE ON/OFF

Article number: N211-K0002-HE935-HA-R60-ZC01_250-S8-###





	3 SDCM
MacAdam	ON/OFF
Controller	
Beam angle	60°
System power Luminaire Efficiency	112 [lm/W]
	11 [W]
	1236 [lm]
Luminous flux	1545 [lm]
Led chip flux	90
CRI	WHITE
Light colour	3500 [K] PREMIUM
LED	СОВ

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

LUMINAIRE

Weight	1,2 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024