


DOWNLIGHT QUNA A MINI 940 11W 15° BLACK PREMIUM WHITE ON/OFF

Article number: N211-K0002-PW940-HA-R15-ZC01_250-S8-###







LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

 Led chip flux
 90

 Luminous flux
 1343 [lm]

 System power
 1074 [lm]

 Luminaire Efficiency
 11 [W]

 Beam angle
 98 [lm/W]

 Controller
 15°

ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 1,2 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour BLACK
Cover Glass
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska