

DOWNLIGHT QUNA A MINI 940 23W 36° BLACK PREMIUM WHITE ON/OFF

Article number: N211-K0002-PW940-HA-R36-ZC02_600-S8-###





Led chip flux	3157 [lm]
Luminous flux	n #
System power	2525 [lm]
· ·	23 [W]
Luminaire Efficiency	110 [lm/W]
Beam angle	36°
Controller	
MacAdam	ON/OFF
	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

LUMINAIRE

Weight	1,2 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 29.06.2024