

## DOWNLIGHT

## DOWNLIGHT QUNA A MINI 930 14W 24° BLACK | ON/OFF

Article number: N211-K0002-RF930-H8-R24-ZC01\_350-S8-###





	LED	COB
	Light colour	3000 [K]
	CRI	90
	Led chip flux	1613 [lm]
	Luminous flux	1290 [lm]
	System power	14 [W]
	Luminaire Efficiency	92 [lm/W]
	Beam angle	24°
	Controller	ON/OFF
	MacAdam	3 SDCM
LUMINAIRE		
	Weight	1,2 [kg]
	5	

## Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 3

+48 32 388 80 00

www.cora.pl cora@cora.pl

IP 20, IK 3,

220-240V 50-60Hz

BLACK

Glass



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 29.06.2024