


DOWNLIGHT QUNA A MINI 820 31W 36° BLACK MEAT PINK ON/OFF

Article number: N211-K0002-VE820-H8-R36-ZC03_800-S8-###







LED COB
Light colour 2000 [K] MEAT PINK

 CRI
 80

 Led chip flux
 2495 [lm]

 Luminous flux
 1996 [lm]

 System power
 31 [W]

 Luminaire Efficiency
 64 [lm/W]

 Beam angle
 36°

 Controller
 ON/OFF

 MacAdam
 3 SDCM

LUMINAIRE

Weight 1,2 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour BLACK
Cover Glass
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements $\pm 1.0\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska