


DOWNLIGHT QUNA A MINI 825 23W 60° BLACK BREAD ON/OFF

Article number: N211-K0002-VF825-H8-R60-ZC02_600-S8-###







LED COB

Light colour 2500 [K] BREAD

CRI 8

 Led chip flux
 2808 [lm]

 Luminous flux
 2246 [lm]

 System power
 23 [W]

 Luminaire Efficiency
 98 [lm/W]

 Beam angle
 60°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 1,2 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska