


DOWNLIGHT QUNA A MINI 825 31W 60° BLACK BREAD ON/OFF

Article number: N211-K0002-VF825-H8-R60-ZC03_800-S8-###



93 [lm/W]





 LED
 COB

 Light colour
 2500 [K] BREAD

 CRI
 80

 Led chip flux
 3621 [Im]

 Luminous flux
 2896 [Im]

 System power
 31 [W]

Beam angle60°ControllerON/OFFMacAdam3 SDCM

LUMINAIRE

Luminaire Efficiency

Weight 1,2 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements $\pm 1.0\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska