


DOWNLIGHT QUNA A MINI 935 25W 60° WHITE HI EFFICIENT ON/OFF

Article number: N211-K0003-BB935-H8-R60-ZC02_650-S8-###



3 SDCM





COB 3500 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 3904 [lm] Luminous flux 3123 [lm] System power 25 [W] Luminaire Efficiency 125 [lm/W] Beam angle 60° Controller ON/OFF

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

LUMINAIRE

MacAdam

Weight 1,2 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour WHITE
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska