


DOWNLIGHT QUNA A MINI 930 14W 36° WHITE PREMIUM WHITE ON/OFF

Article number: N211-K0003-HE930-HA-R36-ZC01_350-S8-###







MacAudin	3 SDCM
MacAdam	ON/OFF
Controller	36°
Beam angle	118 [lm/W]
Luminaire Efficiency	14 [W]
System power	1651 [lm]
Luminous flux	2064 [lm]
Led chip flux	90
CRI	WHITE
Light colour	3000 [K] PREMIUM
LED	СОВ

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

LUMINAIRE

Weight	1,2 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024