


DOWNLIGHT QUNA A MINI 935 23W 24° WHITE PREMIUM WHITE ON/OFF

Article number: N211-K0003-HE935-HA-R24-ZC02_600-S8-###







LED COB

Light colour 3500 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 3513 [lm]

 Luminous flux
 2810 [lm]

 System power
 23 [W]

 Luminaire Efficiency
 122 [lm/W]

 Beam angle
 122 [lm/W]

Controller

MacAdam

24°

ON/OFF

3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

LUMINAIRE

Weight 1,2 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour WHITE
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska