


DOWNLIGHT QUNA A MINI 930 14W 36° WHITE CRI97 ON/OFF

Article number: N211-K0003-HI930-H8-R36-ZC01_350-S8-###







 LED
 COB

 Light colour
 3000 [K] CRI97

CRI 9

Led chip flux 1575 [Im]

Luminous flux 1260 [lm]
System power 14 [W]

Luminaire Efficiency90 [Im/W]Beam angle36°ControllerON/OFF

MacAdam 3 SDCM

LUMINAIRE

Weight 1,2 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour WHITE

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska