


DOWNLIGHT QUNA A MINI 940 27W 15° WHITE PREMIUM WHITE ON/OFF

Article number: N211-K0003-PW940-HA-R15-ZC02_700-S8-###







LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

90 Led chip flux

3634 [lm]
Luminous flux
2907 [lm]

System power 27 [W]

108 [lm/W] Beam angle

15° Controller

ON/OFF MacAdam

3 SDCM

LUMINAIRE

Weight 1,2 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour Glass

Cover 220-240V 50-60Hz

Operating voltage

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.

(€ EM EK

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

Generated: 17.09.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska