


DOWNLIGHT

DOWNLIGHT QUNA A MINI 835 21W 36° WHITE | ON/OFF

Article number: N211-K0003-RF835-H8-R36-ZC02_550-S8-###







LED	COB
Light colour	3500 [K]
CRI	80
Led chip flux	3061 [lm]
Luminous flux	2448 [lm]
System power	21 [W]
Luminaire Efficiency	117 [lm/W]
Beam angle	36°
Controller	ON/OFF
MacAdam	3 SDCM
UMINAIRE	
Weight	1,2 [kg]
Protection rating IP , IK , class	IP 20, IK 3,

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

L

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.

WHITE

Glass

220-240V 50-60Hz





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024