

DOWNLIGHT QUNA A MICRO 942 10W 24° GREY MEAT WHITE ON/OFF

Article number: N212-K0001-CC942-H8-P24-ZC01_250-S9-###



UMINAIRE	
MacAdam	3 SDCM
	ON/OFF
Controller	24°
Beam angle	82 [lm/W]
Luminaire Efficiency	10 [W]
System power	818 [lm]
Luminous flux	1023 [lm]
Led chip flux	90
CRI	WHITE
Light colour	4200 [K] MEAT
LED	СОВ

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 23W.

L

Weight	0.6 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
	GREY
Luminaire colour	
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

