

DOWNLIGHT QUNA A MICRO 940 23W 60° GREY PREMIUM WHITE ON/OFF

Article number: N212-K0001-PW940-HA-P60-ZC02_600-S9-###



mao wan	3 SDCM
MacAdam	ON/OFF
Controller	60°
Beam angle	110 [lm/W]
Luminaire Efficiency	23 [W]
System power	2525 [lm]
Luminous flux	3157 [lm]
Led chip flux	90
CRI	WHITE
Light colour	4000 [K] PREMIUM
LED	СОВ

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 23W.

LUMINAIRE

Weight	0,6 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024