


## DOWNLIGHT QUNA A MICRO 940 14W 24° BLACK PREMIUM WHITE ON/OFF

Article number: N212-K0002-PW940-HA-P24-ZC01\_350-S9-###



100 mm



Ø 136 mm



Ø 125 mm

LED	COB
Light colour	4000 [K] PREMIUM WHITE
CRI	90
Led chip flux	1887 [lm]
Luminous flux	1509 [lm]
System power	14 [W]
Luminaire Efficiency	108 [lm/W]
Beam angle	24°
Controller	ON/OFF
MacAdam	3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 23W.

### LUMINAIRE

Weight	0,6 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska