

DOWNLIGHT QUNA A MICRO 827 19W 24° BLACK | ON/OFF

Article number: N212-K0002-RF827-H8-P24-ZC01_500-S9-###







COB Light colour 2700 [K] | CRI Led chip flux 2694 [lm] Luminous flux 2155 [lm] System power 19 [W] Luminaire Efficiency 113 [lm/W] Beam angle 24° Controller ON/OFF MacAdam 3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 23W.

LUMINAIRE

Weight 0,6 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska