

DOWNLIGHT

## DOWNLIGHT QUNA A MICRO 835 23W 15° BLACK | ON/OFF

Article number: N212-K0002-RF835-H8-P15-ZC02\_600-S9-###



LED	COB	De
Light colour	3500 [K]	LE
CRI	80	ind on
Led chip flux	3340 [lm]	av
Luminous flux	2672 [lm]	
System power	23 [W]	
Luminaire Efficiency	116 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		_
Weight	0,6 [kg]	
Protection rating IP , IK , class	IP 20, IK 3,	1

BLACK

Glass

220-240V 50-60Hz

## Downlight LED

ED downlight for drop ceiling installation. Aluminium housing. Glass cover ncluded. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 23W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

Luminaire colour

Operating voltage

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 29.06.2024