


DOWNLIGHT QUNA A MICRO 957 23W 36° WHITE SPECIAL ON/OFF

Article number: N212-K0003-CC957-H8-P36-ZC02_600-S9-###







LED COB

Light colour 5700 [K] SPECIAL

CRI 90

 Led chip flux
 3023 [lm]

 Luminous flux
 2418 [lm]

 System power
 23 [W]

 Luminaire Efficiency
 105 [lm/W]

Beam angle36°ControllerON/OFFMacAdam3 SDCM

LUMINAIRE

 Weight
 0,6 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 WHITE

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 23W.

Note: All data are typical values. Tolerance of measurements $\pm 1.0\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska