


DOWNLIGHT QUNA A MICRO 930 10W 24° WHITE CRI97 ON/OFF

Article number: N212-K0003-HI930-H8-P24-ZC01_250-S9-###



3 SDCM





COB 3000 [K] CRI97 Light colour CRI Led chip flux 1144 [lm] Luminous flux 915 [lm] System power 10 [W] Luminaire Efficiency 92 [lm/W] Beam angle 24° Controller ON/OFF

LUMINAIRE

MacAdam

 Weight
 0,6 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 WHITE

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 23W.

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska