

DOWNLIGHT

DOWNLIGHT QUNA A MICRO 835 23W 36° WHITE | ON/OFF

Article number: N212-K0003-RF835-H8-P36-ZC02_600-S9-###



LED	COB
Light colour	3500 [K]
CRI	80
Led chip flux	3340 [lm]
Luminous flux	2672 [lm]
System power	23 [W]
Luminaire Efficiency	116 [lm/W]
Beam angle	36°
Controller	ON/OFF
MacAdam	3 SDCM
LUMINAIRE	
Weight	0,6 [kg]

IP 20, IK 3,

220-240V 50-60Hz

WHITE

Glass

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 23W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 29.06.2024