


DOWNLIGHT QUNA A MICRO 840 19W 15° WHITE | ON/OFF

Article number: N212-K0003-RF840-H8-P15-ZC01_500-S9-###



| | |
|----------------------|------------|
| LED | COB |
| Light colour | 4000 [K] |
| CRI | 80 |
| Led chip flux | 2839 [lm] |
| Luminous flux | 2271 [lm] |
| System power | 19 [W] |
| Luminaire Efficiency | 120 [lm/W] |
| Beam angle | 15° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 23W.

LUMINAIRE

| | |
|-----------------------------------|------------------|
| Weight | 0,6 [kg] |
| Protection rating IP , IK , class | IP 20, IK 3, |
| Luminaire colour | WHITE |
| Cover | Glass |
| Operating voltage | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska