


DOWNLIGHT HEKTOR 2 930 27W 15° GREY PREMIUM WHITE ON/OFF

Article number: N213-K0001-HE930-HA-H15-ZC02_700-S6-###



LED	COB
Light colour	3000 [K] PREMIUM WHITE
CRI	
Led chip flux	90
Luminous flux	3911 [lm]
System power	3128 [lm]
Luminaire Efficiency	27 [W]
Beam angle	116 [lm/W]
Controller	15°
MacAdam	ON/OFF
	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight	1.1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10%. System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl

cora@cora.pl



Street: Ignatza Hakuby 18

41-914 Bytom, Polska