

## DOWNLIGHT HEKTOR 2 930 31W 60° GREY CRI97 ON/OFF

Article number: N213-K0001-HI930-H8-H60-ZC03\_800-S6-###



LED	COB
Light colour	3000 [K] CRI97
CRI	90
Led chip flux	3368 [lm]
Luminous flux	2694 [lm]
System power	31 [W]
Luminaire Efficiency	87 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

### LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 16.07.2024



+48 32 388 80 00



www.corra.pl  
cora@corra.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska