


DOWNLIGHT HEKTOR 2 940 25W 45° GREY PREMIUM WHITE ON/OFF

Article number: N213-K0001-PW940-HA-H45-ZC02_650-S6-###



LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 3398 [lm]

 Luminous flux
 2718 [lm]

 System power
 25 [W]

 Luminaire Efficiency
 109 [lm/W]

 Beam angle
 45°

Controller

MacAdam

3 SDCM

LUMINAIRE

 Weight
 1,1 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 GREY

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 18.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska