

DOWNLIGHT

DOWNLIGHT HEKTOR 2 940 19W 45° GREY | ON/OFF

COB

90

4000 [K] |

2416 [lm]

1932 [lm]

102 [lm/W]


ON/OFF

3 SDCM

19 [W]

45°

Article number: N213-K0001-RF940-H8-H45-ZC01_500-S6-###



cutil Ø160mm

Down	light	LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

1	ш	М	IN	Δ	IR	F

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

1,1 [kg]
IP 20, IK 3,
GREY
Glass
220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 18.05.2024