


DOWNLIGHT

DOWNLIGHT HEKTOR 2 930 25W 30° BLACK PREMIUM WHITE ON/OFF

Article number: N213-K0002-HE930-HA-H30-ZC02_650-S6-###



cutout Ø160mm

СОВ	, c
3000 [K] PREMIUM WHITE	L
90	e
3659 [lm]	
2927 [lm]	

25 [W]

30°

117 [lm/W]

ON/OFF

3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Light colour CRI

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 18.05.2024