


## DOWNLIGHT

## DOWNLIGHT HEKTOR 2 940 11W 30° BLACK PREMIUM WHITE ON/OFF

Article number: N213-K0002-PW940-HA-H30-ZC01\_250-S6-###



cutout) Ø160mm

LED	COB
Light colour	4000 [K] PREMIUM WHITE
CRI Led chip flux	90
Luminous flux	1343 [lm]
System power	1074 [lm] 11 [W]
Luminaire Efficiency	98 [lm/W]
Beam angle Controller	30°
MacAdam	ON/OFF
	3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

## LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska