


## DOWNLIGHT

# DOWNLIGHT HEKTOR 2 940 14W 30° BLACK PREMIUM WHITE ON/OFF

Article number: N213-K0002-PW940-HA-H30-ZC01\_350-S6-###



cutout Ø160mm

LED	COB
Light colour	4000 [K] PREMIUM WHITE
CRI	90
Led chip flux	1887 [lm]
Luminous flux	1509 [lm]
System power	1309 [iiii] 14 [W]
Luminaire Efficiency	
Beam angle	108 [lm/W]
Controller	30°
MacAdam	ON/OFF
	3 SDCM

### Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

#### LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl 0

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024