

DOWNLIGHT HEKTOR 2 942 19W 45° WHITE MEAT WHITE ON/OFF

Article number: N213-K0003-CC942-H8-H45-ZC01_500-S6-###



Ø160mm

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LED	COB	
Light colour	4200 [K] MEAT WHITE	
CRI		
Led chip flux	90	
Luminous flux	1976 [lm]	
	1580 [lm]	
System power	19 [W]	
Luminaire Efficiency		
Beam angle	83 [lm/W]	
Controller	45°	
	ON/OFF	
MacAdam	3 SDCM	
UMINAIRE		

LU

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska