

## DOWNLIGHT HEKTOR 2 957 10W 15° WHITE SPECIAL ON/OFF

COR

Article number: N213-K0003-CC957-H8-H15-ZC01\_250-S6-###



cut out Ø160mm

IMINAIBE	
MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	15°
Luminaire Efficiency	105 [lm/W]
System power	10 [W]
Luminous flux	1054 [lm]
Led chip flux	1318 [lm]
CRI	90
Light colour	5700 [K] SPECIAL
LED	COB

#### Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

### LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

#### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 18.05.2024