

DOWNLIGHT HEKTOR 2 957 37W 60° WHITE SPECIAL ON/OFF

Article number: N213-K0003-CC957-H8-H60-ZC03_950-S6-###



Ø160mm

UMINAIRE	
MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	60°
Luminaire Efficiency	99 [lm/W]
System power	37 [W]
Luminous flux	3672 [lm]
Led chip flux	4590 [lm]
CRI	90
Light colour	5700 [K] SPECIAL
LED	СОВ

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska