

DOWNLIGHT HEKTOR 2 930 35W 30° WHITE PREMIUM WHITE ON/OFF

Article number: N213-K0003-HE930-HA-H30-ZC03_900-S6-###



COB

3000 [K] PREMIUM WHITE Light colour

CRI

90 Led chip flux 3911 [lm] Luminous flux 3128 [lm] System power 35 [W] Luminaire Efficiency 89 [lm/W] Beam angle 30° Controller

ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 1,1 [kg] Protection rating IP, IK, class IP 20, IK 3, WHITE Luminaire colour Cover Glass Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska