

DOWNLIGHT HEKTOR 2 935 14W 15° WHITE PREMIUM WHITE ON/OFF

Article number: N213-K0003-HE935-HA-H15-ZC01_350-S6-###



LED COB

Light colour 3500 [K] PREMIUM WHITE

CRI

90 Led chip flux

2131 [lm]

Luminous flux

System power

Luminaire Efficiency

Beam angle

2131 [lm]

1704 [lm]

14 [W]

122 [lm/W]

Controller

MacAdam

15°

ON/OFF

3 SDCM

LUMINAIRE

Weight 1,1 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour WHITE
Cover Glass
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 18.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska