

# DOWNLIGHT HEKTOR 2 935 25W 15° WHITE PREMIUM WHITE ON/OFF

Article number: N213-K0003-HE935-HA-H15-ZC02\_650-S6-###



LED COB

Light colour 3500 [K] PREMIUM CRI WHITE

Led chip flux 90

Luminous flux 3777 [lm] System power 3021 [lm] Luminaire Efficiency 25 [W]

Beam angle 121 [lm/W]

Controller 15°

MacAdam ON/OFF

3 SDCM

#### **LUMINAIRE**

Weight 1.1 [kg] Protection rating IP, IK, class IP 20, IK 3, WHITE Luminaire colour Glass Cover

Operating voltage 220-240V 50-60Hz

### **Downlight LED**

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.









Street: Ignatza Hakuby 18 41-914 Bytom, Polska