

## DOWNLIGHT HEKTOR 2 935 35W 45° WHITE PREMIUM WHITE ON/OFF

Article number: N213-K0003-HE935-HA-H45-ZC03\_900-S6-###



LED	COB
Light colour	3500 [K] PREMIUM WHITE
CRI	90
Led chip flux	4038 [lm]
Luminous flux	3230 [lm]
System power	35 [W]
Luminaire Efficiency	92 [lm/W]
Beam angle	45°
Controller	ON/OFF
MacAdam	3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

### LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 18.05.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska