

DOWNLIGHT HEKTOR 2 935 14W 60° WHITE PREMIUM WHITE ON/OFF

Article number: N213-K0003-HE935-HA-H60-ZC01_350-S6-###



cut out Ø160mm

LED	COB
Light colour	3500 [K] PREMIUM WHITE
CRI	90
Led chip flux Luminous flux	2131 [lm]
System power	1704 [lm]
Luminaire Efficiency	14 [W]
Beam angle	122 [lm/W] 60°
Controller	ON/OFF
MacAdam	3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

