

DOWNLIGHT

DOWNLIGHT HEKTOR 2 930 27W 15° WHITE CRI97 ON/OFF

COB

90

2990 [lm]

2392 [lm]

89 [lm/W]

ON/OFF

3 SDCM

27 [W]

15°

3000 [K] CRI97

Article number: N213-K0003-HI930-H8-H15-ZC02_700-S6-###



cutout Ø160mm

D	ow	nli	gh	t L	ED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LU	мі	NA	IRE

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE				
Weight	1,1 [kg]			
Protection rating IP , IK , class	IP 20, IK 3,			
Luminaire colour	WHITE			
Cover	Glass			
Operating voltage	220-240V 50-60Hz			

0V 50-60Hz

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

Generated: 18.05.2024