

## DOWNLIGHT HEKTOR 2 930 20W 30° WHITE PREMIUM COLOR ON/OFF

Article number: N213-K0003-PC930-HA-H30-ZC01\_500-S6-###



LED COB

Light colour 3000 [K] PREMIUM COLOR

CRI

90 and while flux

 Led chip flux
 2200 [lm]

 Luminous flux
 1760 [lm]

 System power
 20 [W]

 Luminaire Efficiency
 88 [lm/W]

 Beam angle
 30°

 Controller
 30°

MacAdam ON/OFF

## LUMINAIRE

Weight 1,1 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour WHITE

Cover Glass

Operating voltage 220-240V 50-60Hz

## **Downlight LED**

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 18.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska