

DOWNLIGHT HEKTOR 2 930 21W 30° WHITE PREMIUM COLOR ON/OFF

Article number: N213-K0003-PC930-HA-H30-ZC02_550-S6-###



LED COB

Light colour 3000 [K] PREMIUM COLOR

CRI

 Led chip flux
 90

 Luminous flux
 2396 [lm]

 System power
 1916 [lm]

 Luminaire Efficiency
 21 [W]

 Beam angle
 91 [lm/W]

 Controller
 30°

Controller

MacAdam

3 SDCM

LUMINAIRE

 Weight
 1,1 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 WHITE

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska