

## DOWNLIGHT HEKTOR 2 940 23W 30° WHITE PREMIUM WHITE ON/OFF

Article number: N213-K0003-PW940-HA-H30-ZC02\_600-S6-###



cutout Ø160mm

LED	СОВ
Light colour	4000 [K] PREMIUM WHITE
CRI	90
Led chip flux	
Luminous flux	3157 [lm]
System power	2525 [lm]
Luminaire Efficiency	23 [W]
Beam angle	110 [lm/W]
Controller	30°
MacAdam	ON/OFF
WacAdam	3 SDCM

## Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

## LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 18.05.2024