

DOWNLIGHT

DOWNLIGHT HEKTOR 2 940 25W 45° WHITE PREMIUM WHITE ON/OFF

Article number: N213-K0003-PW940-HA-H45-ZC02_650-S6-###



cut out Ø160mm

LED	COB
Light colour	4000 [K] PREMIUM WHITE
CRI Led chip flux	90
Luminous flux	3398 [lm]
System power	2718 [lm]
Luminaire Efficiency	25 [W] 109 [lm/W]
Beam angle	45°
Controller	ON/OFF
	3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

