

DOWNLIGHT

DOWNLIGHT HEKTOR 2 940 11W 60° WHITE PREMIUM WHITE ON/OFF

Article number: N213-K0003-PW940-HA-H60-ZC01_250-S6-###



cutout Ø160mm

Light colour4000 [K] PREMIUM WHTECRI90Led chip flux1343 [lm]Luminous flux1074 [lm]System power11 [W]Luminaire Efficiency98 [lm/W]Beam angle60°ControllerON/OFFMacAdam3 SDCM	LED	COB
90Led chip flux1343 [lm]Luminous flux1074 [lm]System power11 [W]Luminaire Efficiency98 [lm/W]Beam angle60°Controller60°MacAdamON/OFF	Light colour	
Led chip flux1343 [lm]Luminous flux1074 [lm]System power11 [W]Luminaire Efficiency98 [lm/W]Beam angle60°Controller60°MacAdamON/OFF	CRI	90
Luminous flux1074 [lm]System power11 [W]Luminaire Efficiency98 [lm/W]Beam angle60°Controller60°MacAdamON/OFF	Led chip flux	
System power 11 [W] Luminaire Efficiency 98 [Im/W] Beam angle 60° Controller 0N/OFF MacAdam ON/OFF	Luminous flux	1343 [lm]
Luminaire Efficiency 11 [W] Beam angle 98 [lm/W] Controller 60° MacAdam ON/OFF	Custom nouver	1074 [lm]
98 [lm/W] Beam angle Controller MacAdam	System power	11 [W]
Beam angle 60° Controller ON/OFF	Luminaire Efficiency	08 [lm/\/]
Controller ON/OFF	Beam angle	
ON/OFF	Controller	60°
		ON/OFF
	MacAdam	3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

